

SE & LE SERIES SPIN-ON FILTER ELEMENTS

FOR USE WITH SF, DF, MF, MFT & ZDF
SERIES FILTER HEADS



Diameter: 5.1"
 Mounting Thread: 1-1/2"-16 UN
 Pressure: 200 PSI Max. Operating
 ΔP_{max} : 50 PSID
 Temperature: Up to +250°F Operating
 Applications: Petroleum-based fluids.

Part Number	Particle Size	Nominal Rating	Absolute Rating	Can Color / Imprint	Media Type	Free Water Absorption	Overall Height
SE03	3 Micron	$\beta_{<4\mu(c)} = 2$	$\beta_{11\mu(c)} = 75$	White / Green	Cellulose		6.9"
SE10	10 Micron	$\beta_{5\mu(c)} = 2$	$\beta_{19\mu(c)} = 75$	White / Red	Cellulose		6.9"
SE100	141 Micron	-	-	White / Blue	Stn. Steel Mesh		6.9"
SE25	25 Micron	$\beta_{19\mu(c)} = 2$	$\beta_{36\mu(c)} = 75$	White / Black	Cellulose		6.9"
LE03	3 Micron	$\beta_{<4\mu(c)} = 2$	$\beta_{11\mu(c)} = 75$	White / Green	Cellulose		10.9"
LE03AZ	3 Micron	$\beta_{<4\mu(c)} = 2$	$\beta_{11\mu(c)} = 75$	White / Orange	Aqua-Zorb	15 oz.	10.9"
LE10	10 Micron	$\beta_{5\mu(c)} = 2$	$\beta_{19\mu(c)} = 75$	White / Red	Cellulose		10.9"
LE100	141 Micron	-	-	White / Blue	Stn. Steel Mesh		10.9"
LE10AZ	10 Micron	$\beta_{5\mu(c)} = 2$	$\beta_{19\mu(c)} = 75$	White / Orange	Aqua-Zorb	15 oz.	10.9"
LE25	25 Micron	$\beta_{19\mu(c)} = 2$	$\beta_{19\mu(c)} = 75$	White / Black	Cellulose		10.9"

Application Data:

- Reference:
 - $\beta_{x\mu(c)} = 2$ represents 50% efficiency at Particle Size
 - $\beta_{x\mu(c)} = 75$ represents 98.7% efficiency at Particle Size
- Buna-N FG01 gasket standard. Fluorocarbon gasket FG01V optional, consult factory.
- Caution:** Do not use SE/LE Series filter elements on internal combustion engines.
- Aqua-Zorb filter medias absorb and retain free water. Any absorbed water cannot be liberated from the Aqua-Zorb media. As the element becomes saturated with water, the Aqua-Zorb media continues to swell, and will ultimately curtail flow through the filter. Not for use with water-glycols.

Consult Manufacturer for Ordering Information